

Solar 27Q

27x10 W high brightness indoor/outdoor compact wash light

ORDER CODE: **SOLAR27Q**



Solar 27Q is a compact fan-free outdoor wash light featuring an outstanding brightness of 10'832 lumens. Equipped with 27x10 W RGBW / FC LEDs, delivering superior colour mixing. Featuring a slim size as well as the multiple interchangeable optics through magnets, including asymmetrical filters which, all together, make the **Solar 27Q** an incredibly flexible device for indoor use and outdoor. Whilst highly-powerful, the **Solar 27Q** also benefits from being silent.

MAIN FEATURES

- 27x10 W RGBW / FC LEDs, delivering 10'832 lumens
- Compact form factor and fan-free
- Wireless DMX on-board

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 27x10 W RGBW / FC LEDs
- CRI: 71,8
- Luminous flux: @FULL 10'832 lm - with included filter 6'987 lm
- Lux: @FULL (25°) 6'133 lx - with included filter 1'027 lx @3 m full
- Lux: @FULL (25°) 2.208 lx - with included filter 370 lx @5 m full
- Source life expectancy: > 50.000 h

OPTICS

- Beam angle: 25° - with included filter 45°
- Field angle: 39° - with included filter 69°
- Additional optics: 10° / 15° / 45° / 40° filter / 10x60° filter / 30x60° filter
- Other: magnetic filter included to achieve 45° (60° filter), barn door not included

COLOUR SYSTEM

- Colour mixing: RGBW / FC
- CTC: CTC control through independent DMX channel
- Colour wheel: virtual colour wheel with presets

DYNAMIC EFFECTS

- FX generator: section effect with 3 horizontal individually select and control sections
- Static colour mode: selection of static colour
- Manual colour mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment

BODY

- Hardware on-board: magnetic filter frame with 45° filter
- Tilt angle: 0 - 150° with manual regulation
- Body: sturdy die-cast aluminium body conceived for long-time durability
- Body colour: black

CONTROL

- Protocols: DMX512, RDM, W-DMX
- DMX channels: 5 / 7 / 10 / 13 / 17 channel
- W-DMX: included, wireless solution receiver
- RDM: RDM ready for fixture remote monitor and settings

- Display: black OLED high resolution display
 - Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
 - Master/Slave: for synchronized operation of more units linked in a chain
- ### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: different dimming curves available
- Battery backup: battery backup for user operation without connecting to the main power
- Operating temperature: -20° ~ +50°
- Flicker: flicker free frequency with adjustable PWM
- Selectable PWM: 600 ~ 25.000 Hz

ELECTRICAL

- Power supply: 100-240 V – 50/60 Hz
- Power consumption (at 230 V): 268 W
- Power consumption (at 120 V): 275 W
- Output (at 230 V): 9 units on a single power line
- Output (at 120 V): 5 units on a single power line
- Power factor: 0,994

PHYSICAL

- Cooling: natural cooling of the peculiar chassis and to absence of fans
- Suspension and fixing: hanging bracket for floor positioning with "Quick-Lock" system
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Data connection: W-DMX receiver
- Power connection: Seetronic powerCON waterproof IN/OUT connectors
- IP rating: 65 for temporary outdoor application, not for fixed installation
- Dimensions (WxD): 454x269x83 mm
- Weight: 9 kg


ACCESSORIES & RELATED PRODUCTS

- OS25: Quick-Lock omega bracket (included)
- S27QFILTER60: 60° symmetric light diffuser filter for SOLAR27Q (included)
- S27QFILTER40: 40° symmetric light diffuser filter for SOLAR27Q
- S27QFILTER1060: 10x60° asymmetric light diffuser filter for SOLAR27Q
- S27QFILTER3060: 30x60° asymmetric light diffuser filter for SOLAR27Q
- S27QLENS: 10°-15°-45° lens for SOLAR27Q, ARCPD27Q, SOLAR48Q,

- ARCPD48Q, ARCPD15Q and ARCPD96Q
- SUNBLASTFLR: Hanging bracket for SUNBLAST floor positioning, quick-look
- S27QBD: Black barn door 4 directional flaps to adjust the light beam, SOLAR27Q,ARCPD27Q
- FCLS27Q: Flightcase for 6 pcs of SOLAR27Q
- UPBOX1U: Firmware uploader kit, USB IN, 3-pin XLR DMX OUT, USB OUT


COLOUR PRESET FULL ON

Beam angle 25° (45° filter)






COLOUR PRESET FULL ON

Beam angle 45° (45° filter)



TECHICAL DRAWINGS



For more product info and downloads visit our website

