

LumiPar 7IP

7x9 W RGBW compact IP65 LED PAR

ORDER CODE: **LUMIPAR7IP**



LumiPar 7IP is a compact and flexible IP LED PAR made for small concerts and theatres, and to perform as architectural accent luminaire for outdoor events. The housing in die-cast aluminium is designed to feature both as a robust workhorse and totally fan-free being totally silent during its operation.

MAIN FEATURES

- IP65 die-cast aluminium housing
- 7x9 W RGBW LED PAR
- Fan-free and flicker-free operation for IMAG and broadcast

VERSIONS

Code	Beam angle
LUMIPAR7IP20D	20°
LUMIPAR7IP45D	45°

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 7x9 W RGBW LEDs
- Luminous flux: (20°) 2'945 lm - (45°) 3'835 lm
- Lux: (20°) 1'923 lx @3 m full
- Lux: (45°) 654 lx @3 m full
- Source life expectancy: > 50.000 h

OPTICS

- Beam angle: available in 20° or 45°
- Field angle: 36° or 60°

COLOUR SYSTEM

- Colour mixing: RGBW / FC
- White presets: 3.000 K ~ 10.000 K
- Colour wheel: virtual colour wheel with presets
- Macros: built-in white presets

DYNAMIC EFFECTS

- Static colour mode: selection of static colour
- Manual colour mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment

BODY

- Body: sturdy die-cast aluminium body conceived for long-time durability
- Body colour: black

CONTROL

- Protocols: DMX512
- DMX channels: 4 / 6 / 11 channel
- Display: black OLED touch display
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronized operation of more units linked in a chain

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 different dimming curves available
- Strobe / shutter: 0 - 30 Hz, electronic
- Operating temperature: -20° ~ +45°
- Flicker: flicker free operation
- Selectable PWM: 600 ~ 25.000 Hz

ELECTRICAL

- Power supply: 100-240 V – 50/60 Hz
- Power consumption (at 230 V): 65 W
- Power consumption (at 120 V): 64 W
- Output (at 230 V): 58 units on a single power line
- Output (at 120 V): 31 units on a single power line

PHYSICAL


- Cooling: passive cooling and fan-free
- Suspension and fixing: double hanging bracket suitable for safe hanging and for floor positioning
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Power connection: Seetronic powerCON waterproof IN/OUT connectors
- IP rating: 65 for temporary outdoor application, not for fixed installation
- Dimensions (WxHxD): 240x286x154 mm
- Weight: 3,64 kg

ACCESSORIES & RELATED PRODUCTS

- UPBOX1U: Firmware uploader kit, USB IN, 3-pin XLR DMX OUT, USB OUT


COLOUR PRESET FULL ON

Beam angle 20°




COLOUR PRESET FULL ON

Beam angle 45°



TECHICAL DRAWINGS



PROLIGHTS is a trademark of
MUSIC & LIGHTS S.r.l.
musiclights.it

Via A. Olivetti snc
04026 - Minturno (LT) ITALY
Tel: +39 0771 72190



For more product
info and downloads
visit our website



prolights.it
info@prolights.it